





Treadwall® Max6/10 Rotating Walls

The Treadwall Max6/10 combines our widest climbing surface with a lower height designed to fit under a 3 meter ceiling. The Max6/10 features a 6 foot wide by 8 foot tall climbing surface that encourages sideways as well as upward movement. The wall's rotation is powered by the climber's weight - no motors are used. The angle of the surface is adjusted by a lever mounted on the left side. A second lever mounted on the right side adjusts the speed to suit the user, and a patented auto-stop^(tm) mechanism matches the movement of the wall to the climber's movements, gently braking when the climber's feet are at the bottom panel. The Max6/10 fits under a 10 foot ceiling. See the Max6/11 and Max6/12 units for higher ceilings.



SPECIFICATIONS:

Weight: 1050 pounds.

Construction: Steel framework with custom-machined wood panels.

Placement: Inside standard - outside with exterior upgrade.

Width of climbing surface: 6 feet.

Total length of climbing surface: 18 feet.

Number of possible hold placements: 216.

Angle range: positive 10 degrees to negative 35 degrees (overhanging).

Mode of control: Electro-hydraulic braking and resistance.

Electrical requirements: 9 VDC (1500ma) Plug-in transformer (supplied) or battery used.

Electronic Display: Measures distance (feet or meters), time and calories.

Time and distance goals can be pre-set.

Color - frame: Anthracite Gray is standard. Custom colors available.

Color - panels: Natural Wood

Holds: Set of 45 custom training holds in 3 color groups, with optional 14 ladder Line^(tm) holds.


Maximum hold size: 2.5 inches high by 6 inches wide.

Floor Mat: 8 feet x 6 feet custom mat, 1.25 inches dual foam, black 14 oz. vinyl cover.




Warranty: Six years parts, one year electronics and labor.

See full warranty for details.

Treadwall® Max6/11 Rotating Walls



The Treadwall Max6/11 is one of the and most popular Treadwall model. It has a generously sized climbing surface - 6 feet wide by 9 feet high that encourages sideways as well as upward movement. The wall's rotation is powered by the climber's weight - no motors are used. The angle of the surface is adjusted by a lever mounted on the left side. A second lever mounted on the right side adjusts the speed to suit the user, and a patented auto-stop^(tm) mechanism matches the movement of the wall to the climber's movements, gently braking when the climber's feet are at the bottom panel. The standard Max6/11 is designed to fit under an 11 foot ceiling. See the Max6/10 units for lower ceilings and the larger Max6/12 designed specifically for climbing gyms.



SPECIFICATIONS:

Weight: 1100 pounds.

Construction: Steel framework with custom-machined wood panels.

Placement: Inside standard - outside with exterior upgrade.

Width of climbing surface: 6 feet.

Total length of climbing surface: 20 feet.

Number of possible hold placements: 240.

Angle range: positive 10 degrees to negative 35 degrees (overhanging).

Mode of control: Electro-hydraulic braking and resistance.

Electrical requirements: 9 VDC (1500ma) Plug-in transformer (supplied) or battery used.

Electronic Display: Measures distance (feet or meters), time and calories.

Time and distance goals can be pre-set.

Color - frame: Anthracite Gray is standard. Custom colors available.

Color - panels: Natural Wood

Holds: Set of 45 custom training holds in 3 color groups, with optional 14 Ladder Line^(tm) holds.


Maximum hold size: 2.5 inches high by 6 inches wide.

Floor Mat: 8 feet x 6 feet custom mat, 1.25 inches dual foam, black 14 oz. vinyl cover.




Warranty: Six years parts, one year electronics and labor.

See full warranty for details.

Treadwall® Max6/12 Rotating Walls



The Treadwall Max6/12 our largest model, designed specifically for climbing facilities. It has a generously sized climbing surface - 6 foot wide by 10 foot high that encourages sideways as well as upward movement. The wall's rotation is powered by the climber's weight - no motors are used. The angle of the surface is adjusted by a lever mounted on the left side. A second lever mounted on the right side adjusts the speed to suit the user, and a patented auto-stop^(tm) mechanism matches the movement of the wall to the climber's movements, gently braking when the climber's feet are at the bottom panel. The Max6/12 is designed to fit under a 12 foot ceiling. See the Max6/10 and Max 6/11 units for lower ceilings.



SPECIFICATIONS:

Weight: 1150 pounds.

Construction: Steel framework with custom-machined wood panels.

Placement: Inside standard - outside with exterior upgrade.

Width of climbing surface: 6 feet.

Total length of climbing surface: 22 feet.

Number of possible hold placements: 264.

Angle range: positive 10 degrees to negative 35 degrees (overhanging).

Mode of control: Electro-hydraulic braking and resistance.

Electrical requirements: 9 VDC (1500ma) Plug-in transformer (supplied) or battery used.

Electronic Display: Measures distance (feet or meters), time and calories.

Time and distance goals can be pre-set.

Color - frame: Anthracite Gray is standard. Custom colors available.

Color - panels: Natural Wood

Holds: Set of 45 custom training holds in 3 color groups, with optional 14 ladder Line^(tm) holds.

Maximum hold size: 2.5 inches high by 6 inches wide.

Floor Mat: 8 feet x 6 feet custom mat, 1.25 inches dual foam, black 14 oz. vinyl cover.

Warranty: Six years parts, one year electronics and labor.

See full warranty for details.